

TECHNICAL DATA SHEET

1. IDENTIFICATION OF THE PRODUCT AND THE COMPANY

| | |
|----------------------------|--|
| NAME OF THE PRODUCT | MASK '&' UP |
| CODE | 100243 (15 mm) |
| DISTRIBUTOR | BOSSAUTO INNOVA, S.A. |
| ADDRESS | c/ Thomas Edison 16, Apartado de correos 95 |
| CITY | 08430 La Roca del Vallés (Barcelona) SPAIN |
| PHONE | + 34 93 860 49 23 |
| FAX | +34 93 871 23 36 |
| E-MAIL | info@bossauto.com |
| WEB | www.bossauto.com |

2. DESCRIPTION

Tape pre-cut every 38 mm for use in bodywork. The product consists of a paper strip with solvent based adhesive according to the characteristics attached, and a flexible polyester 190my strip, 15 mm wide, attached to one side of the paper tape. The characteristics of the tape allow supporting temperatures up to 80°C and leaves no residue once finished the application. Available only in countries with a valid patent.

3. PROPERTIES

| TEST | AVERAGE | MEASURE UNIT | ACCEPTED RANG | ANALYSIS METHOD |
|---|----------------|------------------|--------------------------|-----------------|
| Thickness . Total . Support | 205 90 | | 195/205 701/110 | PSTC 33 |
| Weight: . Total . Support . Adhesive | 94 59 35 | g/m ² | 86/102 53/65 33/37 | ISO 536 |
| Adhesion: . Iron . Support | 4,8 2,7 | N/25mm | 2,5/ 7,25 1,5/4 | PSTC 1 |
| Adhesion loss (50° 1kg) | 15 | Min. | >5 | SICAD ICQ 10203 |
| Tension force | 87,5 | N/25mm | 70/112,5 | PSTC 31 |

| | | | | |
|-------------------------------------|---|----|------|---------|
| Elongation breakpoint % | 8 | % | 5/11 | PSTC 31 |
| RBT | 1 | cm | 0/3 | PSTC 6 |
| Temperature resistance 30min : 80°C | | | | |

4. APPLICATION

- Plastic strip on a self-adhesive tape facilitating the masking of new windshields and windows.
- Makes masking corners easier.
- Prevents spraying onto rubbers.
- Pre-cut every 38mm for easy application.

5. CONSERVATION

Avoid moisture and extreme brightness. The product keeps initial characteristics 12 months later from production date.

Note: We recommend testing material in relation to the required applications. The company reserves the right to improve or make specific changes and modifications.

6. STANDARD PRESENTATION

Rolls with 10 meters in self-dispensing container. Quantity packed 30 rolls per box. Pre-cut every 38mm.

The technical information is in accordance with our experience. We assure the quality of the product. However, the conditions of use are not under our control and we cannot assume any responsibility of the obtained results.