

Technical information Spot Blender



ColorMatic spot blender is universally applicable for spot blending of 1K and 2K clear coats as well as for 1K and 2K topcoats. It is specially formulated to ensure the overspray will blend into the transition zone, leaving no visible difference between the old and new paintwork. This reduces the need to polish.

Apply ColorMatic 2K Hi-Speed Clear Coats or 2K topcoats to the blended area, immediately after application.

Application:
Ideal for spot repairs.

Quality and properties

- Essential for spot coating
- Additional coating to 1K and 2K, and 1K and 2K clear coats and topcoats
- Simple time-saving processing
- Dissolves well
- Easy to polish
- Significantly reduces the need to polish
- Blends in seamlessly edge areas

Physical and chemical data

- **Basis of binder:** Special resin
- **Colour:** transparent
- **Smell:** solvent
- **Temperature resistance:** to 90°C
- **Storage stability:**
10 years if appropriate storage provided (=10°-25°C, relative air humidity of max. 60%)
- **Size:**
Aerosol cans, maximum nominal volume 400 ml
- **VOC-value:** 283,8g

Environment and labelling

Environmentally compatible: MOTIP DUPLI is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal: Please mind the residue inside the containers. Completely emptied containers can be used for recycling. If cans are not emptied, they should be disposed off as "special refuse".

Labelling: All products of MOTIP DUPLI comply with the current status of their labelling regulations. Classification and distinction takes place by the presently legal form of the **Globally Harmonized System of Classification and Labelling of Chemicals** (GHS) or rather by CLP 1272/2008/EG regulations. Our safety data sheets comply with the current form of REACH 1907/2006/EG, article 31 und appendix II,

Using instructions

Before use, carefully read and observe the warning texts on the label!

- Apply ColorMatic 2K hi-speed clear coat or top coat to the blended immediately after application
- First prepare a matt underlayer in the transition zone with P2000-P4000 abrasive pads.
- **For professional use only**
- **Wear an appropriate respirator (recommended type A2/P3)**

Hints concerning application

For best results, we recommend the application of ColorMatic blender clear approx. 10 cm inside and outside the edge areas.



2 min

thin coats:
2-3

Disclaimer of liability

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. MOTIP DUPLI is let off the liability, unless the liability-based incident is caused by a fault incurred to MOTIP DUPLI.

For any further technical questions call our hotline +49 (0) 62 66 75-266 from Monday to Thursday from 9 h a.m. to 3 h p.m. or on Friday until 12 h p.m.

As of August 9, 2010

This release replaces all eventually earlier issued versions.

Print date: 17.06.2019

MOTIP DUPLI GmbH | Kurt-Vogelsang-Straße 6 | 74855 Haßmersheim | info@de.motipdupli.com