

Technical information Finish Control Spray



ColorMatic finish control spray provides optimum results after polishing the clear coat and topcoat, where appropriate. The micro foam removes oily and waxy polish residue and makes remaining sanding marks visible.

Application:

Ideal for spot repairs and refinishing parts.

Quality and properties

- Removes oily and waxy polish residue
- Makes remaining marks visible
- Easy and fast application
- Mild, non-aggressive cleaning agent
- Very time saving
- Used after polishing sanded coated surface (dust inclusions, paint defects, frosted edges)

Physical and chemical data

- **Basis of binder:** Acrylic
- **Colour:** transparent, foaming
- **Smell:** solvent
- **Efficiency:**
Depending on consistence and colour of the ground:
400 ml are sufficient for approx. 2,0 m²
- **Substrate:**
Sanded and polished clearcoat or topcoat surface
- **Drying-time (at 20°C, 50% relative air humidity):**
Dust-dry: after approx. 10 minutes
Dry to touch: after approx. 30 minutes
The drying time depends on surrounding temperature, air humidity and thickness of the applied coat.
- **Temperature resistance:** to 80°C
- **Storage stability:**
10 years if appropriate storage provided (=10°-25°C, relative air humidity of max. 60%)
- **Size:**
Aerosol cans, maximum nominal volume 400 ml
- **VOC-value:** 89,7g

Environment and labelling

Environmentally compatible: MOTIP DUPLI is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal: Please mind the residue inside the containers. Completely emptied containers can be used for recycling. If cans are not emptied, they should be disposed off as "special refuse".

Labelling: All products of MOTIP DUPLI comply with the current status of their labelling regulations. Classification and distinction takes place by the presently legal form of the **Globally Harmonized System of Classification and Labelling of Chemicals** (GHS) or rather by CLP 1272/2008/EG regulations. Our safety data sheets comply with the current form of REACH 1907/2006/EG, article 31 und appendix II,

Using instructions

Before use, carefully read and observe the warning texts on the label!

- Apply a thin layer on the polished surface
- Wipe dry with a clean, soft cloth (do not leave to dry)
- If sanding marks or holograms are visible, polishing is required
- Repeat above procedure until results are perfect
- **For professional use only**

Hints concerning application

ColorMatic finish control spray exposes even holograms that have developed during polishing work. Just use after polishing as instructed.



2 min

1

Disclaimer of liability

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and

do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. MOTIP DUPLI is let off the liability, unless the liability-based incident is caused by a fault incurred to MOTIP DUPLI.

For any further technical questions call our hotline +49 (0) 62 66 75-266 from Monday to Thursday from 9 h a.m. to 3 h p.m. or on Friday until 12 h p.m.

As of July 26, 2010
This release replaces all eventually earlier issued versions.

Print date: 17.06.2019

MOTIP DUPLI GmbH | Kurt-Vogelsang-Straße 6 | 74855 Haßmersheim | info@de.motipdupli.com