

Technical Information Carpet Spray Paint



ColorMatic Carpet spray paint is a user friendly spray for the color refreshment and coloring of textile car mats and carpets in the sector of cars and utility vehicles. Simple and quick laminating of stains and color wears. Provides high coverage and good adhesion. Applicable on textile mats and through specific additives also on rubber car mats.

Application:

For the color refreshments and coloring of textile mats and carpets in cars and utility vehicles.

Quality and properties

- High-quality acrylic coat
- Simple application
- User-friendly restoration of wears on textile car mats and carpets
- Laminates stains and wears
- Applicable on textile and rubber car mats
- Tip: After every spray pass we recommend to rework the still wet lacquer film with a brush so the carpet fibres are throughout moistened with color and will not stick together.

Physical and chemical data

- **Basis of binder:** Acrylic
- **Colour:** Black and anthracite
- **Smell:** solvent
- **Efficiency:**
Depending on consistence and colour of the ground:
400 ml are sufficient for approx. 1,25 - 1,75 m²
- **Drying time (at 20°C, 50% relative air humidity):**
Dust-dry: after approx. 5 min
Dry to touch: after 30 min
The drying time depends on surrounding temperature, air humidity and thickness of the applied coat.
- **Temperature resistance:** to 90°C
- **Storage stability:**
10 years if appropriate storage provided (=10°-25°C, relative air humidity of max. 60%)
- **Size:**
Aerosol cans, maximum nominal volume 400 ml
- **VOC-value:** 238 g

Environment and labelling

Environmentally compatible: MOTIP DUPLI is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.


Disposal: Please mind the residue inside the containers. Completely emptied containers can be used for recycling. If cans are not emptied, they should be disposed off as "special refuse".

Labelling: All products of MOTIP DUPLI comply with the current status of their labelling regulations. Classification and distinction takes place by the presently legal form of the **Globally Harmonized System of Classification and Labelling of Chemicals** (GHS) or rather by CLP 1272/2008/EG regulations. Our safety data sheets comply with the current form of REACH 1907/2006/EG, article 31 und appendix II,

Using instructions

Before use, carefully read and observe the warning texts on the label!

- Surfaces should be free of dust
- Shake can well for 2 minutes
- Carry out spray test
- Spray several thin coats at intervals of 5 minute
- Tip: After every spray pass we recommend to rework the still wet lacquer film with a brush so the carpet fibres are throughout moistened with color and will not stick together.
- **For professional use only**
- **Wear an appropriate respirator (recommended type A2/P3)**



Disclaimer of liability

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. MOTIP DUPLI is let off the liability, unless the liability-based incident is caused by a fault incurred to MOTIP DUPLI.

For any further technical questions call our hotline +49 (0) 62 66 75-266 from Monday to Thursday from 9 h a.m. to 3 h p.m. or on Friday until 12 h p.m.

As of February 1, 2016

This release replaces all eventually earlier issued versions

Print date: 17.06.2019

MOTIP DUPLI GmbH | Kurt-Vogelsang-Straße 6 | 74855 Haßmersheim | info@de.motipdupli.com